

# PRODUCT SPECIFICATIONS

## Commercial Smooth Non-PVC Wallcoverings

### FOR PRODUCTS

#### Smooth Non-PVC Murals

### PHYSICAL PROPERTIES

**DESCRIPTION** ..... Type II, 17 mil Eco-Friendly PVC-Free Wallcovering

**CONSTRUCTION** ..... Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks

#### SUBSTRATE

Roll Width ..... 54' (1.37 m)

Weight ..... 290 g/m<sup>2</sup> per TAPPI T-410 Test Method

Face ..... Latex-Saturated Wet-Strength Paper

Backing ..... Textile Scrim

#### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

### MOLD & MILDEW

Highly Resistant – GREENGUARD Test method, GGTM.P040 per guidelines of ASTM D6329

### FLAME & SMOKE

#### SUBSTRATE

ASTM-E84 ..... Class A Fire Rated

Compliant with California Fire Code CA 1237

Compliant with IBC (International Building Code) sec. 803.1.1

### SPECIFICATIONS

EN233 – Spongeability rating (wave 1), Excellent color fastness rating. Carries the CE certification according to European Standard EN15102.

### ENVIRONMENTAL

REACH compliant

FSC®-certified paper

Compliant with CHPS Section 01350