

PRODUCT SPECIFICATIONS

Commercial Textured Non-PVC Wallcoverings

FOR PRODUCTS

Textured Non-PVC Murals

PHYSICAL PROPERTIES

DESCRIPTION	Type II, 14 oz. Eco-Friendly PVC-Free Wallcovering
CONSTRUCTION	Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks

SUBSTRATE

Roll Width	54' (1.37 m)
Weight	14 oz. per lineal yard (22 mil)
Face	Polyester/Natural Fiber Technology
Backing	Nonwoven 31% Post-Consumer Recycled Content

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

MOLD & MILDEW

ASTM E96 Permeability, 66 Perms Dry Cup Method, Passed WA-101 8 Perms

FLAME & SMOKE

SUBSTRATE

ASTM-E84	Class A
CAN/ULC-S102	Passed requirements

SPECIFICATIONS

WA Specifications:
WA-101, Type II, Passed requirements
NSF/ANSI-342, Certified for Silver compliance

ENVIRONMENTAL

Low-VOC
Prop 65 Compliant
Compliant with CHPS Section 01350
Recycled Content, 31% Post-Consumer
Free of PVC and POA (Olefin) Plasticizers, Phthalates, formaldehyde, Chlorine, Halogen, Heavy-Metals (Cadmium, Mercury, Lead, Zinc) Ozone Depleting Chemicals and Brominated flame retardants

LEED ELIGIBILITY

Product may contribute up to 2 LEED credits, conditionally, 2 other credits
MR Credit 4.1 Recycled Content 20%
MR Credit 4.2 Recycled Content 30%
Conditionally
MR Credit 2.1 Contribution to project recycling program
MR Credit 2.2 Contribution to project recycling program
MR Credit 5.1 Manufactured local to new construction
EQ Credit 4.1 Mounted with low emitting adhesives