

PRODUCT SPECIFICATIONS

Commercial Textured White Vinyl Wallcoverings

FOR PRODUCTS

Textured White Vinyl Murals with ImageLock®
Semi-Smooth White Vinyl Murals with ImageLock®

Canvas Emboss White Vinyl Murals with ImageLock®
Wood Grain Emboss White Vinyl Murals with ImageLock®

PHYSICAL PROPERTIES

DESCRIPTION Category V, Type II 20 oz. PVC-Vinyl Wallcovering

CONSTRUCTION Osnaburg-Backed Textured Vinyl with UV-LED Inks

SUBSTRATE

Roll Width 54' (1.37 m)
Weight 20 oz. per lineal yard
Face Textured PVC-Vinyl
Backing Polyester/Cotton Osnaburg

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

WASHABILITY & SCRUBABILITY

ASTM F793 Standard Classification of Wallcovering by Characteristics
Washability para. 7.4, 100 cycles: Passed all requirements
Scrubability para. 7.7, 300 cycles: Passed all requirements

MOLD & MILDEW

ASTM G21 Passed requirements

FLAME & SMOKE

SUBSTRATE

ASTM-E84 Class A
EU Class Flame (EN15102), B-s1
CAN/ULC-S102.2 Passed requirements
BS476 Parts 6&7 Passed requirements

SPECIFICATIONS

Federal Specifications:
GSA CCC-408-D, Type II
WA Specifications:
WA-101, Type II
NSF/ANSI-342, Certified for Silver compliance
NFPA Life Safety Code 101
Passed requirements for flame and smoke

ENVIRONMENTAL

Low-VOC
EU Toxicity compliant
California Prop 65 compliant
Phthalate free, Cadmium and Lead-Free