

PRODUCT SPECIFICATIONS

High Performance Smooth Non-PVC Wallcoverings

FOR PRODUCTS

Smooth Non-PVC Murals with ImageLock®

PHYSICAL PROPERTIES

DESCRIPTION Type II, 17 mil Eco-Friendly PVC-Free Wallcovering

CONSTRUCTION Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks and UV Matte Coating

SUBSTRATE

Roll Width 54" (1.37 m)

Weight 290 g/m² per TAPPI T-410 Test Method

Face Latex-Saturated Wet-Strength Paper

Backing Textile Scrim

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

MOLD & MILDEW

Highly Resistant – GREENGUARD Test method, GGTM.P040 per guidelines of ASTM D6329

FLAME & SMOKE

ASTM-E84..... Class A Fire Rated

Compliant with California Fire Code CA 1237

Compliant with IBC (International Building Code) sec. 803.1.1

SPECIFICATIONS

EN233 – Spongeability rating (wave 1), Excellent color fastness rating. Carries the CE certification according to European Standard EN15102.

ENVIRONMENTAL

REACH compliant

FSC®-certified paper

Compliant with CHPS Section 01350