

# PRODUCT SPECIFICATIONS

## High Performance Textured Non-PVC Wallcoverings

### FOR PRODUCTS

Textured Non-PVC Murals with ImageLock®

### PHYSICAL PROPERTIES

**DESCRIPTION** ..... Type II, 14 oz. Eco-Friendly PVC-Free Wallcovering

**CONSTRUCTION** ..... Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks and UV Matte Coating

#### SUBSTRATE

Roll Width ..... 54" (1.37 m)

Weight ..... 14 oz. per lineal yard (22 mil)

Face ..... Polyester/Natural Fiber Technology

Backing ..... Nonwoven 31% Post-Consumer Recycled Content

#### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

#### COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

### MOLD & MILDEW

ASTM E96 Permeability, 66 Perms Dry Cup Method, Passed WA-101 8 Perms

### FLAME & SMOKE

ASTM-E84 ..... Class A

CAN/ULC-S102 ..... Passed requirements

### SPECIFICATIONS

WA Specifications:

WA-101, Type II, Passed requirements

NSF/ANSI-342, Certified for Silver compliance

### ENVIRONMENTAL

Low-VOC

Prop 65 Compliant

Compliant with CHPS Section 01350

Recycled Content, 31% Post-Consumer

Free of PVC and POA (Olefin) Plasticizers, Phthalates, formaldehyde, Chlorine, Halogen, Heavy-Metals (Cadmium, Mercury, Lead, Zinc) Ozone Depleting Chemicals and Brominated flame retardants

### LEED ELIGIBILITY

Product may contribute up to 2 LEED credits, conditionally, 2 other credits

MR Credit 4.1 Recycled Content 20%

MR Credit 4.2 Recycled Content 30%

Conditionally

MR Credit 2.1 Contribution to project recycling program

MR Credit 2.2 Contribution to project recycling program

MR Credit 5.1 Manufactured local to new construction

EQ Credit 4.1 Mounted with low emitting adhesives