

# PRODUCT SPECIFICATIONS

## High Performance Textured White Vinyl Wallcoverings

### FOR PRODUCTS

Textured White Vinyl Murals with ImageLock®  
Semi-Smooth White Vinyl Murals with ImageLock®

Canvas Emboss White Vinyl Murals with ImageLock®  
Wood Grain Emboss White Vinyl Murals with ImageLock®

### PHYSICAL PROPERTIES

**DESCRIPTION** ..... Category V, Type II 20 oz. PVC-Vinyl Wallcovering

**CONSTRUCTION** ..... Osnaburg-Backed Textured Vinyl with UV-LED Inks and UV Matte coating

#### SUBSTRATE

Roll Width ..... 54' (1.37 m)  
Weight ..... 20 oz. per lineal yard  
Face ..... Textured PVC-Vinyl  
Backing ..... Polyester/Cotton Osnaburg

#### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

#### COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

### WASHABILITY & SCRUBABILITY

ASTM F793 Standard Classification of Wallcovering by Characteristics  
Washability para. 7.4, 100 cycles: Passed all requirements  
Scrubability para. 7.7, 300 cycles: Passed all requirements

### MOLD & MILDEW

ASTM G21 ..... Passed requirements

### FLAME & SMOKE

ASTM-E84 ..... Class A  
Flame Spread ..... 25  
Smoke Developed ..... 140  
EU Class Flame (EN15102), B-s1  
CAN/ULC-S102.2 ..... Passed requirements  
BS476 Parts 6&7 ..... Passed requirements

### SPECIFICATIONS

Federal Specifications:  
GSA CCC-408-D, Type II  
WA Specifications:  
WA-101, Type II  
NSF/ANSI-342, Certified for Silver compliance  
NFPA Life Safety Code 101  
Passed requirements for flame and smoke

### ENVIRONMENTAL

Low-VOC  
EU Toxicity compliant  
California Prop 65 compliant  
Phthalate free, Cadmium and Lead-Free